

Model		Pressure Range	Capacity [m³/h]				Absorbed Power [kW]*				Nominal Power [kW]*		Noise [db(A)]		Dimension [mm]			Weight [kg]
			bar(g)	min	50 Hz	60 Hz	max	min	50 Hz	60 Hz	max	50 Hz	60 Hz	50 Hz	60 Hz	L	W	
A10	A10.4	2,5 - 4,5	51	70	83	83	4	5	6	6	5,5	7,5	72	73	1.275	706	1.600	370
	A10.8	6 - 8	49	68	75	75	5	7	9	9	7,5	11						
A20	A20.4	2,5 - 4,5	78	107	127	127	5	9	10	10	9	11	72	73	1.550	845	1.725	550
	A20.8	6 - 8	77	84	99	116	8	9	11	14	11	15						
A30	A30.4	2,5 - 4,5	127	176	208	208	9	14	17	17	15	18,5	72	73	1.550	845	1.725	550
	A30.8	6 - 8	122	169	190	190	12	18	21	21	18,5	22						
A35	A35.4	2,5 - 4,5	152	211	250	250	11	18	22	22	18,5	22	73	74	1.620	845	1.775	710
	A35.8	6 - 8	181	205	231	252	15	19	26	27	22	30						
A60	A60.4	2,5 - 4,5	263	364	431	431	19	30	36	36	30	37	73	74	2.065	1.080	2.060	1.015
	A60.8	6 - 8	257	356	409	430	24	36	43	44	37	45						
A90	A90.4	2,5 - 4,5	406	563	667	667	29	45	54	54	45	55	73	74	2.065	1.080	2.150	1.870
	A90.8	6 - 8	396	550	635	667	35	53	63	69	55	75						
A120	A120.4	2,5 - 4,5	623	865	996	996	47	72	86	86	75	90	74	75	2.065	1.080	2.150	1.970
	A120.8	6 - 8	551	765	879	879	50	74	89	89	75	90						
A150	A150.4	2,5 - 4,5	762	1.030	1.215	1.215	61	88	109	109	90	110	77	78	2.570	1.570	2.000	2.100
	A150.8	6 - 8	630	875	1.030	1.030	63	90	111	111	90	110						
A180	A180.4	2,5 - 4,5	1.076	1.495	1.719	1.719	78	119	152	152	132	160	78	79	3.320	1.770	2.200	3.900
	A180.8	6 - 8	907	1.054	1.200	1.240	84	103	120	124	110	132						
	A180.8 S		868	-	-	1.447	84	-	-	152	160	160						
A260	A260.4	2,5 - 4,5	1.290	1.775	2.090	2.090	104	153	186	186	160	200	79	80	3.320	1.770	2.200	3.900
	A260.8	6 - 8	868	1.447	1.737	1.737	84	152	194	194	160	200						
A400	A400.4	2,5 - 4,5	1.662	2.322	-	2.540	134	197	-	222	200	250	79	80	4.000	2.250	2.330	5.900
	A400.8	6 - 8	1.620	2.131	-	2.301	161	238	-	262	250	250						
A460	A460.4	2,5 - 4,5	1.076	2.990	3.438	3.438	78	241	308	308	320	320	79	80	5.000	2.250	2.460	8.330
	A460.8	6 - 8	868	-	-	2.895	84	-	-	320	320	320						
A520	A520.4	2,5 - 4,5	1.290	3.550	4.180	4.180	104	320	392	392	400	400	79	80	5.000	2.550	2.460	9.100
	A520.8	6 - 8	868	2.895	3.474	3.474	84	320	400	400	400	400						
A800	A800.4	2,5 - 4,5	1.662	4.644	-	5.080	134	394	-	444	500	500	79	80	5.200	3.700	2.330	10.900
	A800.8	6 - 8	1.620	4.262	-	4.602	161	476	-	524	500	500						

Hz = frequency | m³/h = compressed air flow rate at 3,5 and 7 bar(g) | Standard reference conform to ISO 8778 : 1 bar(a), 20°C, 65% Relative Humidity | Performance according to ISO 1217 : 2009 (E), Annex C.

\* Total machine absorbed power with class IE3 efficiency electric motors, all auxiliaries included.

FOR MORE INFORMATION:

INFO@PNEUMOFORE.COM - WWW.PNEUMOFORE.COM

Pneumofore has the right to implement changes and improvements to the described technical data any time either for technical or marketing reasons. Pneumofore® trademark and logo are registered worldwide. © Pneumofore - all rights reserved - it is strictly forbidden to make unauthorised copies of this document.

